

# HEAVY GREASE



- Pressure resistant lubricant (NLGI 2).
- Transparent.
- Protection against corrosion.
- Silicone-free.
- Acid-free.
- Steam-resistant.
- Operating temperature -26°C to +190°C.
- NSF-H1 tested for the food industry, nr. 153012.

## Applications:

- Approved for use in the food industry as per the NSF-H1 registration.
- Has a super strong resistance to moisture, steam, heat, cold and has a strong carrying capacity.
- Industrial machinery with heavy load on the transmission mechanisms.
- Long-term lubricant for:
  - Heavy chains
  - Extendable arms
  - Container elevator
  - Guides on cranes and boats
  - Threaded rods industrial machinery
  - Threaded rods door train/tram/bus
  - Lift truck
  - Train exchange
  - Locks

<u>Art.No.</u>	<u>Product</u>	<u>Content</u>
E100006	HEAVY GREASE	500 ml.

## TECHNICAL SPECS

Color:	Transparent
Odor:	Neutral
Flash point:	> 200°C
Drop point:	250°C
Density:	0,94 kg/m <sup>3</sup>
4 ball weld load:	250 daN (circa 255 kg)
Basic oil:	Minérale
Basic oil viscosity:	160 mm <sup>2</sup> /s

## Directions

Shake well before application. Spray uniformly with short intervals. When possible move the fitting parts gently while spraying.

The information and images are as accurate as possible. Users should ensure that their product is suitable for the chosen application. Multitask Industries does not guarantee the accuracy or completeness of the information. Please refer to our Terms and Conditions. Multitask Industries shall under no circumstances be liable for any indirect, incidental or consequential damage arising from the sale, resale, use or misuse of the product.