

# HIGH-TECH PRIMER



- Extreme performance coating.
- Dries ultra quickly.
- HIGH-TECH PRIMER is perfectly sprayable.
- Provides high-performance anti-corrosion protection.
- Can be applied before or after welding.
- Can be painted over.

## Applications:

Can be applied:

- steel
- aluminium
- zinc-coated steel

<u>Art.No.</u>	<u>Product</u>	<u>Content</u>
H100110	HIGH-TECH PRIMER ROOD	400 ML.
H100111	HIGH-TECH PRIMER GRIJS	400 ML.

## TECHNICAL SPECS

Color HIGH-TECH PRIMER ROOD:	Matte red
Color HIGH-TECH PRIMER GRIJS:	Matte gray
Drying time:	Dust dry after ± 10 min. (20°C) Tack-free after ± 20 min. (20°C) Can be painted over after ± 1,5 hours. (20°C)
Recommended coating thickness:	14 - 20 micron
Composition:	Mixture of active substance with propellant.
VOS/VOC:	HIGH-TECH PRIMER ROOD: 621 g/l HIGH-TECH PRIMER GRIJS: 620 g/l

## Instructions for use:

Remove any grease and dust from the treatable surface with MT<sub>CLEANER</sub>. Leave to dry. Shake well before use. Spraying distance 30 cm. Apply in one single thin layer. Turn the canister upside down after use and spray-clean the nozzle. Leave to dry.

The information and images are as accurate as possible. Users should ensure that their product is suitable for the chosen application. Multitask Industries does not guarantee the accuracy or completeness of the information. Please refer to our Terms and Conditions. Multitask Industries shall under no circumstances be liable for any indirect, incidental or consequential damage arising from the sale, resale, use or misuse of the product.