

VULCANISÉ+



Properties:

- Vulcanising tape, black color.
- Protective foil provided.
- Protects against corrosion.
- Good electrical properties.
- High stability under all working circumstances.
- Supports immersion in water for long stretches.
- Good ozone resistance.
- Durable.
- Easy and quick to apply.
- Reacts by stretching.
- Can be applied to grease surfaces.

Applications:

- Ideal for applications that do not support a heat source.
- Repairs can be made without the need for disassembly.
- Cable sheathing.
- Wire connections.
- Protection against abrasions.
- Protection against corrosion, e.g. metal tubes,...
- Protection and sealing of irregular shapes.
- Insulation of electrical connections.
- Enhancing water resistance.
- Weather resistant.
- Joining or separating power or distribution cables.



VULCANISÉ+



Durable.
Easy and quick to apply.
Reacts by stretching.
Can be applied to greasy surfaces.

Art.No.	Product	Size	Wall thickness
B100104	VULCANISÉ+	19 mm x 10 m	0,5 mm
B100105	VULCANISÉ+	25 mm x 10 m	0,5 mm
B100106	VULCANISÉ+	38 mm x 10 m	0,5 mm

TECHNICAL SPECS

Material:	Polyisobutylene rubber
Thickness:	0,5 mm
Elongation up to breaking point:	900 % (BS 903)
Waterproof:	Yes
Volume resistivity:	10 ¹³ Ohm/cm (ASTM D 257)
Dielectric strength:	42 kV/mm (ASTM D 149)
Tensile strength:	2,0 MPa (BS 903)
Processing temperature:	-40°C to +90°C
Ozone resistance:	Excellent
Chemical resistance:	Water vapor, corrosion vapor, diluted acids
Not chemically resistant:	Petroleum, cleaning agents, grease, oil
Adhesion method:	Self-amalgamating