

# 2 KOMP STRUKTUUR



- Unique and professional 2 component adhesive for structural bonding and sealing.
- Processing time 4 à 6 minutes.
- Dry and sandable after 60 minutes.
- Can be painted.
- Temperature -50°C to +200°C (peak +220°C)
- Highly chemical resistant.

## Applications:

- Due to structural bonding, the resulting tensile and shock test results make this product to market leader in a MAXIMUM number of application areas.
- Both for repair and manufacture.
- For indeterminate surfaces such as:
  - Stainless steel
  - Aluminium
  - Fibreglass
  - Polycarbonate
  - ABS
  - PVC
  - Polyester
  - Carbon steel
  - Wood
  - Natural stone
  - Vinyl
  - Acrylates
  - GRP
  - Urethanes

SMALL CARTRIDGE  
LITTLE LOS

# 2 KOMP STRUKTUUR



Art.Nr.	Product	Color	Content
D100051	2 KOMP STRUKTUUR	Beige	50 ml
D101000	MIXERTIP 50 ml.		

## TECHNICAL SPECS

Odor:	Strong acid
Processing time:	4 to 6 minutes
Shelf life:	12 months (5°C to 25°C)
Elongation at break:	3500 psi
Tensile strength:	24 MPa
Hardness:	75 Shore D
Filler:	1 to 4 mm
Temperature range:	-50°C to +200°C (peak +220°C)

## Instructions for use

Abrade the surface (if needed mechanized with low speed). Clean the surface with MT<sub>CLEANER</sub> for treatment on stone, aluminium,... For the treatment of plastic, clean with PLAST<sub>CLEAN</sub>. Spray a small amount before mouting the nozzle MIXERTIP (ART. D101000) (this to become a good mixing ratio). Apply the glue close to the touch surface (for avoiding air bubbles).