

FAST TOP LEVEL



- Super fast professional 2 components adhesive for bonding and sealing.
- Processing time to 30 seconds.
- Dry after 1 minute.
- Sandable after 10 minutes.
- Overcoatable.
- Temperature -40°C to +100°C (peak +150°C).
- Based on PU.
- Ideal for fast repairs.

Applications:

- FAST TOP LEVEL is a high quality 2 component polyurethane adhesive. It is a strong adhesive that can be used with small, fast and durable adhesion and repair work due to its exceptional properties mix (very fast dry, fast sandable and overcoatable).
- Attaches very well on indeterminate surfaces such as:
 - Stainless steel
 - Wood
 - Natural stone
 - Polycarbonate
 - ABS
 - PVC
 - Aluminium

SMALL CARTRIDGE
LITTLE LOS

FAST TOP LEVEL



<u>Art.Nr.</u>	<u>Product</u>	<u>Color</u>	<u>Content</u>
D100055	FAST TOP LEVEL	Black	50 ML
D101000	MIXERTIP 50 ML		

TECHNICAL SPECS

Odor:	None to light amino acid
Shelf life:	24 months (15°C - 32°C)
Elongation at break:	75%
Tensile strength:	27 MPa (+23°C)
Hardness:	60 Shore D
Filler:	1 to 4 mm
Temperature range:	-40°C to +100°C (peak +150°C)
Holes stuffing:	Ja
Processing time:	To 30 seconds

Instructions for use

Abrade the surface (if needed mechanized with low speed). Clean the surface with MT_{CLEANER} for treatment on stone, aluminium,... For the treatment of plastic, clean with PLAST_{CLEAN}. If necessary prepare the surface with MT_{PRIMER}. Spray a small amount before mouting the nozzle MIXERTIP (ART. D101000) (this to become a good mixing ratio). Apply the glue close to the touch surface (for avoiding air bubbles).