

ANTISLIP



- Prevents slipping on smooth surfaces.
- Easy to apply.
- Adherent.
- Flexible. (Bends to 90°)

Applications:

Can be applied on different surfaces and the applications are very different.

- Stairs (wood, natural stone, metal)
- Smooth floors (wood, concrete,...)
- Borderline (industry)
- Terrace (attraction parks)

TECHNICAL SPECS

Bonding:	Acrylic glue
Wearer:	0,1 mm PVC
Minerals:	Aluminium Oxide
Adhesion on steel (PSTC-4):	0,63 gr/cm ²
Tensile strength(PSTC-31):	2,6 gr/cm ²
Elongation at break:	> 25%
Flexibility:	Bends to 90°
Lifetime:	3 à 5 years at normal rate
Temperature range:	-30°C to +80°C
Resistance to:	
Water (PSTC-35):	Excellent > 10 months
Chemicals (PSTC-35):	Excellent > 8 months
Motor oil (PSTC-35) :	Excellent > 30 hours

Instructions for use

Degrease the surface with MT_{CLEANER}. On difficult or very porous surfaces, pre-treatment with MT_{PRIMER}. The surface must be dry. Take the desired length of the ANTISLIP, remove the protective foil and stick on the desired place.

The information and images are as accurate as possible. Users should ensure that their product is suitable for the chosen application. Multitask Industries does not guarantee the accuracy or completeness of the information. Please refer to our Terms and Conditions. Multitask Industries shall under no circumstances be liable for any indirect, incidental or consequential damage arising from the sale, resale, use or misuse of the product.