

# CLEAR GREASE



- Approved for the food industry NSF-H1, no. 140162.
- Anti-wear (contains PTFE).
- Anti-corrosion.
- Non-acidic.
- Electrically non-conductive.
- Water resistant.
- Temperature range -20°C to +170°C (peak +220°C)
- Reduces stick-slip and pitting.

## Applications:

Due to its extreme high-quality, the product can be used in the food industry, agricultural machinery, transport, general industry and construction sector. Ideal for:

All types of conductors	High peripheral speeds	Chains
Rods	Cables	Power systems
Bearings	Open and closed systems	Mounting rubbers
Mounting of antennas	Silent blocks	Battery terminals

Art.No.	Product	Content
E100010	CLEAR GREASE KOKER	400 gr
E100013	CLEAR GREASE POT	2,5 kg

## TECHNICAL SPECS

Color:	White - Transparent
Composition:	Medicinal oil, thickener, PTFE, adhesive.
Density:	ca. 0,90
NLGI grade:	1-2
Thermal stability:	Good
Temperature range:	-20°C to +170°C (Peak +220°C)
Drop point:	>250°C
EP performance 4-ball test, load:	3924N

## Instructions for use

400 gr. cartridge: Before use, remove the lid and pull off the lip.

Pot 2.5 kg: Remove the lid before use.

Do not mix with bentonite grease or sodium grease! Read the technical and safety specifications.

NLGI grade 1-2.

The information and images are as accurate as possible. Users should ensure that their product is suitable for the chosen application. Multitask Industries does not guarantee the accuracy or completeness of the information. Please refer to our Terms and Conditions. Multitask Industries shall under no circumstances be liable for any indirect, incidental or consequential damage arising from the sale, resale, use or misuse of the product.